

Table 3.1.1.3.B (IP)  
**ZONE 2 - Compliance Packages for Space Heating Equipment with  $84\% \leq \text{AFUE} < 92\%$**   
 Forming Part of Sentence 3.1.1.3.(2)

Component	Thermal Values <sup>(6)</sup>	Compliance Package					
		B1	B2	B3	B4	B5	B6
Ceiling with Attic Space	Min. Nominal R <sup>(1)</sup>	50	60	60 + HH	60 + HH	50	60
	Max. U <sup>(2)</sup>	0.020	0.017	0.016	0.016	0.020	0.017
	Min. Effective R <sup>(2)</sup>	49.23	59.22	59.90	59.90	49.23	59.22
Ceiling Without Attic Space	Min. Nominal R <sup>(1)</sup>	31	31	31	31	31	31
	Max. U <sup>(2)</sup>	0.036	0.036	0.036	0.036	0.036	0.036
	Min. Effective R <sup>(2)</sup>	27.65	27.65	27.65	27.65	27.65	27.65
Exposed Floor	Min. Nominal R <sup>(1)</sup>	35	31	31 + 10 ci	31	35	31
	Max. U <sup>(3)</sup>	0.031	0.034	0.025	0.034	0.031	0.034
	Min. Effective R <sup>(3)</sup>	32.02	29.80	39.80	29.80	32.02	29.80
Walls Above Grade	Min. Nominal R <sup>(1)</sup>	22 + 7.5 ci	22 + 7.5 ci	22 + 10 ci			
	Max. U <sup>(3)</sup>	0.042	0.042	0.038	0.038	0.038	0.038
	Min. Effective R <sup>(3)</sup>	23.90	23.90	26.40	26.40	26.40	26.40
<i>Basement Walls</i> <sup>(6)</sup>	Min. Nominal R <sup>(1)</sup>	20 ci	12 + 10 ci	20 + 10 ci	20 + 10 ci	20 + 12 ci	20 + 12 ci
	Max. U <sup>(4)</sup>	0.047	0.048	0.040	0.040	0.037	0.037
	Min. Effective R <sup>(4)</sup>	21.12	20.84	25.15	25.15	26.69	26.69
Below Grade Slab Entire Surface > 600 mm Below Grade	Min. Nominal R <sup>(1)</sup>	—	5	10	10	5	5
	Max. U <sup>(4)</sup>	—	0.163	0.090	0.090	0.163	0.163
	Min. Effective R <sup>(4)</sup>	—	6.13	11.13	11.13	6.13	6.13
Heated Slab or Slab ≤ 600 mm Below Grade	Min. Nominal R <sup>(1)</sup>	10	10	10	10	10	10
	Max. U <sup>(4)</sup>	0.090	0.090	0.090	0.090	0.090	0.090
	Min. Effective R <sup>(4)</sup>	11.13	11.13	11.13	11.13	11.13	11.13
Edge of Below Grade Slab ≤ 600 mm Below Grade	Min. Nominal R <sup>(1)</sup>	10	10	10	10	10	10
Windows and Sliding Glass Doors	Max. U <sup>(5)</sup>	0.21	0.28	0.25	0.25	0.25	0.21
	Energy Rating	34	25	29	29	29	34
Skylights	Max. U <sup>(5)</sup>	0.49	0.49	0.49	0.49	0.49	0.49
Space Heating Equipment	Min. AFUE	90%	90%	87%	87%	84%	84%
HRV	Min. SRE	75%	81%	70%	75%	81%	81%
Domestic Water Heater <sup>(7)</sup>	Min. EF	0.66	0.66	0.66	0.62	0.66	—
Column 1	2	3	4	5	6	7	8

**Notes to Table 3.1.1.3.B (IP):**

The following definition applies:

HH = 10 inch high heel

- (1) The values listed are minimum Nominal R values for the thermal insulation component only.
- (2) U-Value and effective R value shall include entire ceiling assembly components, from interior air film to vented space air film above insulation.
- (3) U-Value and effective R value shall include entire exposed floor or above grade wall assembly components, from interior air film to exterior air film.
- (4) U-Value and effective R value shall include entire *basement* wall or slab assembly components and interior air film.
- (5) U-Value is the *overall coefficient of heat transfer* for a window assembly, sliding glass door assembly or skylight assembly expressed in Btu/(h·ft<sup>2</sup>·F).
- (6) In the case of *basement* wall assemblies, where R20 ci is required R12 + 10 ci is permitted to be used or vice versa; or where R12 + 5 ci is required, R15 ci is permitted to be used or vice versa.
- (7) If an EF of a water tank is not indicated in a compliance package, there is no EF requirement for water tank for that specific compliance package.
- (8) Nominal and effective R values are expressed in (h·ft<sup>2</sup>·F)/Btu. U-Values are expressed in Btu/(h·ft<sup>2</sup>·F).